



AQUA PLAST ACRYLIC PREMIUM PUTTY

(Water Based Acrylic Wall Putty)

Aqua Plast Acrylic Premium Putty is a ready to use water based acrylic wall putty for interiors in the paste form. It is one of the best products of its kind available in the market which provides a very strong and durable finish. It has excellent adhesion to the surface and provides quality walls and ceilings for residential or commercial constructions.

WHERE TO USE: Aqua Plast Acrylic Premium Putty should be directly applied on the surface/interior walls and ceilings with painter's knife or mason's steel trowel.

HOW TO USE:

(A) SURFACE PREPARATION: New plaster surfaces should be allowed to mature for min. 3 months. Ensure the surface is clean, dry and free from loose particles, dust, dirt, grease, wax etc. Surface imperfection/ dents/cracks should be repaired before application.

(B) METHOD OF APPLICATION: Aqua Plast Acrylic Premium Putty is ready to use and no need of dilution. Use the fine steel trowel or painter's putty knife to spread Aquaplast Premium covering the maximum surface area. The thickness of the coat should be 1 mm. After the first coat of Aquaplast Premium is dried apply a thin second coat. Thickness of both the coats should not exceed 2 mm. The drying time of each coat is around 3-4 hours. After the application and dried of final coat, smoothen the surface by rubbing gently with a '0' number sand paper or emery paper. Remove the dust using clean cloth. The Aquaplast Premium surface is now ready for painting.

COVERAGE: A 20kg bucket covers approximately 125-150 sq.ft. for a coating of 2mm thickness.

ADVANTAGES:

- It is excellent for filling and smoothening out cracks and dents on plastered wall
- It has special acrylic binders that ensure that it retains a strong grip on the wall surface.
- It is also enhances breathability and lesser porosity compared to conventional putty.
- It has superior workability, ensures ease of application for fast work execution.

- It has better alkali resistance, thus making it more suitable for new walls.
- It can be applied on almost all interior surfaces new or old
- It is quick drying, thus ensuring faster completion of jobs

STORAGE: Store in cool and dry place. Protect from direct sunlight and rain during storage and in transit. Aqua Plast Acrylic Premium Putty when partly consumed, the remaining material in the bucket should be kept air tight

PRECAUTION: After completion of work, clean tools and vessels with water before material sets. Never apply more than 2mm at a time and do not apply more than 3mm thickness in any circumstances.

SHELF LIFE:	PACKAGING:
For better results use within 6 months from the date of manufacturing.	1, 2, 5kg cans & 10, 20kg bucket.

TECHNICAL SPECIFICATIONS:

PARAMETERS	RESULT
Colour	White
Nature	Ready to use thick paste
Finish	Smooth and even finish
Drying time	Surface dry time 30 min
Coverage	100 Sq.ft/ 25kg bag for 2 coat at 2mm thickness
Mode of application	Steel palti or trowel

Corporate Office:

601, Corporate Arena, Off. Aarey Piralal Cross Rd., Goregaon (W), Mumbai - 400104
 Tel: 022-46038393 Email: info@aquaproofindia.com | Website: www.aquaproofindia.com