



TYLE GROUT

(Cementitious Tile Joint Filler)

Tyle Grout is the finest cement based tile grouting filler ready mix powder, manufactured by experts in the field. It is available in a range of 30 beautiful shades with 1kg and ½kg pouches. It is a powder form material which requires only addition of water before use.

WHERE TO USE: It can be applied over internal, external floor & wall tile joints.

HOW TO APPLY:

(A) SURFACE PREPARATION: Joints in which Tyle Grout is to be applied should be cleaned and made free from any contaminants which will affect adhesion.

(B) MIXING: Tyle Grout premix powder should be used for filling any type of tile joints only after 24 hours of fixing the tiles. Mix Tyle Grout with water in the ratio of three part powder and one part water by volume. Let the mixed paste of Tyle Grout remain in the pan for 10 to 15 minutes. Apply the paste to fill joints with a sponge/squeegee. Remove surplus paste of Tyle Grout with a damp sponge before it dry. Allow the Tyle Grout to naturally cure (completely dry) for 24 hours after application.

(C) APPLICATION: Mix Tyle Grout with water. Apply by hand or with squeegee. Clean tile area after 2 hours by sponge and by TyleKleen after 24 hours.

COVERAGE: 1kg pack will cover area in sq.ft. as per the tile sizes (ref. shade card).

ADVANTAGES:

- It is durable and imparts excellent water resistance and water proofing properties.
- It does not shrink or cause cavities which accumulate dirt.
- It has excellent scratch and mark resistance.
- It is a do-it-yourself product and thus application is very simple and easy.
- Tyle Grout with range of colors adds the aesthetic beauty to the floors and walls which are tile.
- It is durable & economical.

STORAGE: Store unopened in normal & dry condition.

COVERAGE CHART: One kg. pack of TyleGrout is enough to cover the following areas in square feet as per tile size and joint widths given below.

TILE SIZE	TILE JOINT WIDTH			
25x25x6mm	2.1	1.1	0.8	0.7
100x100x12mm	5.4	2.7	1.8	1.4
200x200x9mm	10.8	5.5	3.7	2.8
400x400x9mm	21.6	10.8	7.3	5.5

SHELF LIFE:

For better result use within one year, from the date of manufacturing.

PACKAGING:

500gm & 1kg pouches with 12 pouches in master carton & 10kg bag.

**Corporate Office:**

601, Corporate Arena, Off. Aarey Piramal Cross Rd., Goregaon (W), Mumbai - 400104
Tel: 022-46038393 Email: | info@aquaproofindia.com | Website: www.aquaproofindia.com