



TYLE-O-FIX™

(Tile Fixing Admixture)

Tyle-O-Fix is a white polymer based liquid additive used to make mortars of high bond strength. The mortar so made is waterproof and can be used for fixing ceramic, marble, cement tiles etc. on floors and walls.

WHERE TO USE: For fixing tiles over tiles, floors & cladding for all types of cement, glazed and ceramic tiles.

HOW TO USE: Thoroughly clean the surface on which the tiles are to be fixed with a wire brush hammer or a scraping machine. Dry mix cement and fine sand in the proportion of 1:2. To this mixture add Tyle-O-Fix in the ratio of 7.5 liters per 50kg of cement and mix thoroughly by adding water to get a uniform mortar of thick consistency. Apply the prepared mortar at 3mm thickness. While the mortar is still fresh, press the tiles onto the mortar in ordinary tile fixing manner.

ADVANTAGES:

- It is an admixture in a cement/sand mortar in a ratio of 1:2.
- It is easy to use.
- Better adhesion.
- It is very economical.
- Also, it is chemically resistant.
- It is flexible and resistant to thermal impact, shock and is non-toxic.

STORAGE: Store unopened in normal & dry condition.

DOSAGE: 1Ltr of liquid per bag of cement mortar in 1:2 ratio and covers approximately 18 sq.ft. at 3mm thickness.

SHELF LIFE:

For better result use within one year,
from the date of manufacturing.

PACKAGING:

5, 10 & 20Ltr Drum.

TECHNICAL SPECIFICATIONS:

PROPERTIES	RESULT
Physical appearance	Milky white liquid
Solubility	Fully miscible with water
Density	1.03 ± 0.01
pH	8 - 9
Toxicity	Non - toxic
Anti - foam	Yes

**Corporate Office:**

601, Corporate Arena, Off. Aarey Piralal Cross Rd., Goregaon (W), Mumbai - 400104
Tel: 022-46038393 Email: info@aquaproofindia.com | Website: www.aquaproofindia.com